



www.mobilelifts.com

What lift is best for you?

Dur-A-Lift has been manufacturing truck mounted aerial lifts, for what is better known as a bucket truck, since 1969. We offer a wide variety of models for a variety of industries and applications. Here is a breakdown of what we have to offer.

USE THIS GUIDE TO FIND THE RIGHT LIFT FOR YOU.

1 - AERIAL LIFT SERIES

START BY NARROWING DOWN WHICH AERIAL LIFT SERIES BEST SUITS YOUR NEEDS.

DPM2 & DLT2 - telescopic articulating, material handling or personnel aerial lift with 180° basket rotator, basket elevator and top mounted jib and winch

DPM - telescopic articulating, material handling or personnel aerial lift with 180° basket rotator and side mounted jib and winch

DTAX - telescopic articulating, aerial lift with 180° basket rotator

DTA - telescopic articulating aerial lift

DHT - heavy duty, telescopic aerial lift

DT - telescopic aerial lift

DVS - telescopic aerial lift for use with enclosed body (van series)

DO - articulating, overcenter aerial lift

DFSL - articulating, non-overcenter aerial lift

DAT3 - telescopic articulating, non-overcenter forestry aerial lift

Urban Forestry Unit - telescopic articulating forestry truck with chipper box

DCP - telescopic articulating cable placer unit

Material handling? Personnel?
Telescopic? Articulated? Both?
Insulated? Non-insulated?
One person basket? Two person basket?

		Telescopic	Articulating	Material Handling Option	Maximum Working Height	Maximum Side Reach	Insulated Option	Non-Insulated Option	2-person Basket Option	180° Basket Rotator	Basket Elevator Option	Basket Mount Style
TELESCOPIC ARTICULATED	DLT2	✓	✓	✓	67'	39' 2"	✓	✓	✓	✓	✓	
	DPM2	✓	✓*	✓	39' - 59'	31' 6"	✓	✓	✓	✓	✓	
	DPM	✓	✓*	✓	37' - 57'	31' 6"	✓	✓	✓	✓		
	DTAX	✓	✓		44' - 49'	30'	✓	✓		✓		
	DTA	✓	✓		40' - 45'	29' 6"	✓	✓				Side / End
TELESCOPIC	DHT	✓			35' - 39'	26'	✓	✓		✓		
	DT	✓			34'	22' 3"	✓	✓				Side / End
VAN	DVS	✓			34'	21'		✓				Side / End
ARTICULATED	DO		✓		37' - 41'	30' 4"	✓	✓				Side
	DFSL		✓		34' - 38'	19' 10"	✓	✓				Side
FORESTRY	DAT3	✓	✓		65' - 75'	48'	✓					End
	UFU <small>DTAX-40/45</small>	✓	✓		45' - 50'	30'	✓	✓		✓		
CABLE PLACER	DCP	✓	✓		41'	26' 6"		✓				

*Models DPM2-32 and DPM-32 are telescopic only

2 MODEL NUMBERS

HERE IS A BREAKDOWN OF ALL THE MODELS AVAILABLE WITH SPECIFICATIONS.

Model Number	Lift Type	Max Height	Max Side Reach	Stow Height	Insulated Option	Non-Insulated Option	2 Person Basket Available	Extension Travel	Main Boom Travel	Articulating Arm Travel	Lower Boom Travel	Upper Boom Travel	Lift Weight
DLT2-60	TA(M)*	67'	39' 2"	12'	✓	✓	✓	134"	-26° to 75°	0° to 91°	-	-	5950#
DPM2-52	TA(M)*	59'	31' 6"	11' 8"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4400#
DPM2-47	TA(M)*	54'	31' 6"	10' 5"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4300#
DPM2-40	TA(M)*	47'	31' 6"	10' 6"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	3900#
DPM2-36	TA(M)*	43'	27' 6"	10' 6"	✓	✓	✓	96"	-30° to 75°	0° to 75°	-	-	3700#
DPM2-32	T(M)*	39'	25' 4"	10' 8"	✓	✓	✓	120"	-15° to 80°	-	-	-	3300#
DPM-52	TA(M)*	57'	31' 6"	11' 8"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4400#
DPM-47	TA(M)*	52'	31' 6"	10' 5"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4300#
DPM-40	TA(M)*	45'	31' 6"	10' 6"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	3900#
DPM-36	TA(M)*	41'	27' 6"	10' 6"	✓	✓	✓	96"	-30° to 75°	0° to 75°	-	-	3700#
DPM-32	T(M)*	37'	25' 4"	10' 8"	✓	✓	✓	120"	-15° to 80°	-	-	-	3300#
DTAX-44	TA	49'	30'	10'	✓	✓		122.5"	-25° to 78°	0° to 82°	-	-	2800#
DTAX-42	TA	47'	28'	10'	✓	✓		110.5"	-25° to 78°	0° to 82°	-	-	2665#
DTAX-39	TA	44'	28'	10'	✓	✓		110.5"	-25° to 78°	-2° to 81°	-	-	2450#
DTA-40	TA	45'	29' 6"	10'	✓	✓		122.5"	-25° to 78°	0° to 82°	-	-	2750#
DTA-38	TA	43'	27' 6"	10'	✓	✓		110.5"	-25° to 78°	0° to 82°	-	-	2615#
DTA-35	TA	40'	27' 6"	10'	✓	✓		110.5"	-25° to 78°	-2° to 81°	-	-	2400#
DHT-34	T	39'	26'	9' 10"	✓	✓		128"	-22° to 82°	-	-	-	2700#
DHT-32	T	37'	24'	9' 10"	✓	✓		104"	-22° to 82°	-	-	-	2700#
DHT-30	T	35'	22'	9' 10"	✓	✓		104"	-22° to 82°	-	-	-	2600#
DT-29	T	34'	22' 3"	10' 6"	✓	✓		108"	-25° to 78°	-	-	-	1900#
DVS-29	T	34'	21'	10' 1"		✓		108"	-5° to 80°	-	-	-	2000#
DO-36	A	41'	30' 4"	9' 8"	✓	✓		-	-	-	0° to 100°	0° to 196°	2500#
DO-32	A	37'	26' 4"	9' 8"	✓	✓		-	-	-	0° to 100°	0° to 196°	2400#
DFSL-36	A	38'	19' 10"	10'	✓	✓		-	-	-	0° to 92°	0° to 133°	1950#
DFSL-32	A	34'	17' 10"	10'	✓	✓		-	-	-	0° to 92°	0° to 133°	1800#
DAT3-70	TA	75'	48'	12' 4"	✓			180"	-	-	0° to 95°	0° to 165°	8300#
DAT3-60	TA	65'	41' 3"	12' 4"	✓			144"	-	-	0° to 95°	0° to 165°	6800#
UFU^{DTAX-45}	TA	50'	30'	11' 3"	✓	✓		122.5"	-25° to 78°	0° to 82°	-	-	2800#
UFU^{DTAX-40}	TA	45'	28'	11' 2"	✓	✓		110.5"	-25° to 78°	-2° to 81°	-	-	2450#
DCP-36	TA	41'	26' 6"	10' 1"		✓		110.5"	-25° to 75°	-6° to 83°	-	-	2675#

T = Telescopic A = Articulating M = Material handling * Can be configured with or without material handling capabilities



3 INSULATED VS NON-INSULATED

The letter 'S' at the end of a model name signifies steel, meaning it is the non-insulated version of that lift. Anything without an 'S' is fiberglass. For example: DTAX is the insulated (fiberglass) version and DTAXS is the non-insulated (steel) version. Many of our lifts are available in both versions. The model names are as follows:

- DLT2 → DLT2S**
- DTAX → DTAXS**
- DT → DTS**
- DFSL → DSL***
- DPM2 → DPM2S**
- DTA → DTAS**
- DVS (steel only)**
- DO → DOS**
- DPM → DPMS**
- DHT → DHTS**

*The DFSL doesn't follow the standard non-insulated naming system. The F stands for fiberglass

4 BASKET STYLES/ TYPES OF CONTROLS

You may occasionally notice a series of letters at the end of a lift name, these signify either the basket style or the types of controls used to run the lift. For example: DPM-36 DU or DTAX-45 FP. Here are what the letters stand for and where you may see them used:

TYPE OF CONTROLS

Here are the types of controls and what models they are available with. For example you may see DTAS-35 FP or DTAS-35 IS.

- DC** - Drive (battery) controls
- TS** - Two speed controls
- FP** - Full pressure controls

	DC	TS	FP
DLT2 & DLT2S			✓
DPM2 & DPM2S			✓
DPM & DPMS			✓
DTAX & DTAXS			✓
DTA			✓
DTAS	✓	✓	✓
DHT & DHTS			✓
DT			✓
DTS	✓	✓	✓
DVS	✓	✓	
DO & DOS			✓
DFSL	✓	✓	✓
DAT3			✓

BASKET STYLES

(APPLIES TO DPM, DPM2 and DLT2)

Our material handling aerial lifts are available with several basket styles. Since all of these lifts have full pressure (FP) controls the model name instead includes the basket style designation. For example: DPM-47 DU or DPM2-52 MH. Here is a breakdown of what the basket style abbreviations stand for:



- DP** - dual person, personnel
- DU** - dual configuration (dual person, personnel OR single person, material handling)
- MH** - single person, material handling
- SP*** - single person, personnel

*SP is available on DPM-36 and DPM-40 only